ORWAK COMPACT 3115

COMPACT

THE ORWAK COMPACT 3115 is ideal for small volumes of plastic foil, but is also designed for cardboard compaction. A material selector makes the choice easy! The cross-binding function gives a tight grip of the bale and is helpful for compaction of soft plastic or small pieces of material.



Cross-binding





Orwak benefits

MORE PRODUCTIVE USE OF TIME

Less time spent on waste handling, more time for your core activities!

MORE SPACE & ORDER

Our balers rapidly minimize the space the waste takes up, keeping aisles free and tidy.

LESS COSTS, MORE VALUE

More compaction = less waste volume to transport. Fewer transports required results in lower transportation costs and reduced CO₂ emissions. Sorting at source yields a higher quality of waste material for recycling.



Why Orwak Compact?

- + Strong compaction on the spot! Requires little space, yet provides effective volume reduction
- + Easy-to-handle light weight bales
- + The best choice for small to medium size volumes of cardboard and plastic



ORWAK COMPACT 3115

Compact and versatile baler

- fits where you need it!

PREPARED FOR CROSS-BINDING


3115 is designed for cross-binding, a function that helps secure the bales and one that is particularly useful when compacting small pieces of material.

AUTOSTART FOR EFFICIENT COMPACTION

An autostart function allows the baler to start compacting the material as soon as you close the door.

MATERIAL SELECTOR

A material selector makes the choice between compacting cardboard and plastic easy.



ORWAK COMPACT 3115 IS OPTIMIZED FOR:

PAPER PLASTIC FOIL

+ Cardboard + Shrink film + Shredded paper + Plastic bags

+ Paper sacks

OTHER METALS OTHER PLASTICS + Steel straps + Plastic straps

ADJUSTABLE BALE SIZE


The cardboard bales weigh up to 60 kg and 3115 offers three different sizes of bale height for more options in waste management.

SILENT OPERATION CONTRIBUTES TO A BETTER WORKING ENVIRONMENT

Thanks to a silent type of hydraulics, the sound emission is low, which contributes to improving the working environment for the employees and is an important feature if the baler is installed close to customers.

DIMENSIONS & SPECIFICATIONS

DIMENSIONS								
А	В	С	D	E				
1990 mm	940 mm	790 mm	1535 mm	650 mm				



Weight (machine) Total: 380 kg

TECHNICAL SPECIFICATIONS											
LOADING APERTURE	CYCLE TIME	PRESS FORCE	BALE SIZE	BALE WEIGHT	NOISE LEVEL	PROTECTION CLASS	OPERATING POWER				
Width: 800 mm Height: 460 mm	33 secs	HP 6 ton, 60 kN LP 4 ton, 40 kN	Width: 800 mm Depth: 600 mm Height: 600 mm	Cardboard: Up to 60 kg Plastic: Up to 85 kg	57 db (A)	IP 55	Single Phase 230 V, 50 Hz, 10 A				



