

SAFETY JOGGER

PATRICK

Product sheet
dimber S3



Product reference	CLIMBER
Euronorm EN345	S3 SRC
Sizes	47-38
Weight(s. 41)	640 gr.

Model Description: Leather shoe, water repellent, black, Cambrella lining, antistatic, puncture resistant SJ FLEX sole, shock proof, anti-slip, composite toe, S3, double density PU sole.

Application areas: industries.

Precaution and maintenance of the shoe: To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, neither nearby a heat source.

		Description	Measure unit	Result	EN345 required
Complete shoe	Protection of toes: composite tip resistant to: » a shock of 200 J » pressure of 1500 kg	Impact resistance (Clearance after Shock)	mm	17,5	>14
		Compressive strength (after clearance compression)	mm	17	>14
	Anti-Shock system: Low-Density polyurethane And profile of the heel	Shock absorption in heel	J	>34	>20
Upper	Leather, water repellent, black/grey thickness 1,6mm	Permeability to water vapor	mg/m ² hour	>2,7	>0,8
		Permeability coefficient	mg/cm ²	>25	>20
		Water repellent	minute	>20	<60
Front	Thickness 1,2mm	Permeability coefficient	mg/cm ²	>35	>30
Lining	Cambrella black	Permeability to water vapor	mg/cm ² hour	>5	>2
Back	Thickness 1,0mm	Permeability coefficient	mg/cm ²	>45	>30
Insole	Antistatic, absorbent, resistant to abrasion and to exfoliation	Abrasion resistance	cycles	>400	>400
Outsole	Antistatic double density polyurethane injected directly onto the PU upper black, anti-slip, abrasion resistant, mineral oils and weak acids	Abrasion resistance(volume loss)	mm ³	110	<150
		Oil resistance(volumen variation AV)	%	1,0+	<12+
		Coefficient of adhesion of the outsole	---	0,18	>0,15



SiTco
TOTAL PACKAGING SOLUTIONS

شركة الفصول للتجارة والصناعة الدولية

SEASON INTERNATIONAL TRADING & INDUSTRIES CO.

P.O. Box 886, Manama - Kingdom of Bahrain, Tel: +973 17704647, Fax: +973 17704648
E-mail: info@seasoninternational.net, web: www.seasoninternational.net