

The technologically advanced and versatile wrapping solution



Characteristics

Ring diameters:	50 cm	90 cm	125 cm	160 cm	200/250 cm
Standard film quality:	23 m μ	23 m μ	23 m μ	23 m μ	23 m μ
Film reel dimensions:	100 mm	100, 170, 250 mm	100, 170, 250 mm	100, 170, 250 mm	100, 170, 250 mm
Max. ring speed:	350 rpm	140 rpm	70 rpm	60 rpm	50 rpm
Power supply:	230 V	230/400 V	230/400 V	230/400 V	230/400 V
Power consumption:	0.40 Kw	1.58 Kw	1.61 Kw	1.63 Kw	1.66 Kw
Inverter / PLC:	Fuji / Omron	Fuji / Omron	Fuji / Omron	Fuji / Omron	Fuji / Omron

Advantages

- CE certified
- Proven quality with competitive price
- Easy operation, simple maintenance
- In various inner ring diameters available
- Double film reel dispenser
- Ring protection
- Adjustable stretch film tension
- Automatic film cutter and clamp
- Adjustable ring speed
- Touch screen panel
- Various optional features, i.e.
 - Top press
 - Dispensers

Chart of types model FV350

Item No.	Model	Inner diameter
31.30 11	FV350 /50	50 cm
31.301 2	FV350 /90	90 cm
31.301 3	FV350 /125	125 cm
31.301 4	FV350 /160	160 cm
31.301 5	FV350 /200	200 cm
31.301 6	FV350 /250	250 cm



SiTCO
TOTAL PACKAGING SOLUTIONS

شركة الفصول للتجارة والصناعة الدولية
SEASON INTERNATIONAL TRADING & INDUSTRIES CO.

P.O. Box 886, Manama - Kingdom of Bahrain, Tel: +973 17704647, Fax: +973 17704648
E-mail: info@seasoninternational.net, web: www.seasoninternational.net