



## Chart of types strapping head MH610

Item No.	Model	Strap widths		Strap thicknesses		Max. Tension	
		mm	inch	mm	inch	N	lbs
47.5610	MH610/25-32/0.40-0.59/7.0/PET	25-32	1-1¼	0.40-0.59	.016-.023	7000	1545
47.5611	MH610/25-32/0.60-0.75/7.0/PET	25-32	1-1¼	0.60-0.75	.024-.030	7000	1545
47.5612	MH610/25-32/0.80-1.35/7.0/PET	25-32	1-1¼	0.80-1.35	.031-.053	7000	1545
47.5613	MH610/25-32/0.40-0.59/2.5/PET	25-32	1-1¼	0.40-0.59	.016-.023	2500	560
47.5614	MH610/25-32/0.60-0.75/2.5/PET	25-32	1-1¼	0.60-0.75	.024-.030	2500	560

## Features

- Compact and modular design
- One piece of a luminium cast housing
- High strap tension up to 7000 N (1545 lbs) adjustable
- 25mm or 32mm strap width usable, a djustable without changing parts
- S strap gu ide open feat ure
- Well proven separate feeding, tensioning and friction weld sealing systems
- High consistent seal efficiency because of environment temperature monitoring
- Use of state-of-the-art manufacturing, controlling and material technology
- Three side suspension points and plug connections for ea sy integration
- Long life and maintenance friendly, resulting in high a vailabiltiy

## Options

- Dispenser for jumbo-coils
- S word
- Telescopic arch
- Movable machine
- Side sealing machine
- Head suspension with power floating system
- Edge protection feed systems top and bottom
- Bunk feed system with various magazines
- Vertical and lateral press systems up to 80 KN
- Conveying systems
- Turntable for cross strapping
- Mechanical pack detectin sensor
- Thinner or rubber coated base protection plate
- S strap gu ide arch systems
- Control
- Cycle counter inside the head
- Dust cleaning system
- Counter

**SITCO**  
TOTAL PACKAGING SOLUTIONS

شركة الفصول للتجارة والصناعة الدولية

SEASON INTERNATIONAL TRADING &amp; INDUSTRIES CO.

P.O. Box 886, Manama - Kingdom of Bahrain, Tel: +973 17704647, Fax: +973 17704648  
E-mail: info@seasoninternational.net, web: www.seasoninternational.net