

Manual plastic strapping tools



Characteristics

Strapping qualities:	Polypropylene (PP) and Polyester (PET)
Strapping dimensions:	widths 15.0 – 16.0 mm / $\frac{5}{8}$ "
thicknesses	0.50 – 0.90 mm / .020 - .035"
Weights:	3.8 kg / 8.4 lbs without suspension
	3.9 kg / 8.6 lbs with suspension
Average seal strength:	approx. 70 %
Type of joint:	Joint with special seals
Suspension (Optional):	bolt and grip ball for horizontal applications; have to be ordered separately

Advantages

- Handy light weight tensioning and sealing tool to strap flat packages (i.e. pallets, bales, crates, cases, various packages) using plastic strapping
- A reliable, robust and service – friendly tool
- The windless tensioning system allows very high strap tension
- Special serrated seals and the patented sealing force balance system guarantee a very high seal joint efficiency
- The sealing handle is always operated until it hits the stop – thus the seal efficiency of all joints is high and balanced

Chart of types model P 404

Item No.	Model	Width		Thicknesses	
		mm	inch	mm	inch
43.0404	P 404 /15-16/0.50-0.90	15-16	5/8"	0.50-0.90	.020-.035

Seals

Item No.	Model	Width		Contents of carton in pcs.	Weight	
		mm	inch		kg	lbs
41.5082	P 404 /16	15-16	5/8"	1000	9.3	20.5

Accessories

P 40.2046 Handle for horizontal applications
(Grip ball and bolt)

**SiTCO**
TOTAL PACKAGING SOLUTIONS

شركة الفصول للتجارة والصناعة الدولية

SEASON INTERNATIONAL TRADING & INDUSTRIES CO.

P.O. Box 886, Manama - Kingdom of Bahrain, Tel: +973 17704647, Fax: +973 17704648
E-mail: info@seasoninternational.net, web: www.seasoninternational.net