

SAFETY JOGGER

PATRICK

Product sheet
x0600 S3



Product reference	X0600
Euronorm EN345	S3 SRC
Sizes	47-36
Weight(s. 41)	580 gr.

Model Description: Leather shoe, water repellent, black, Cambrella lining, antistatic, Puncture resistant sole, shock proof, anti-slip, steel toe, S3, PU sole.

Application areas: food, healthcare, industries.

Precaution and maintenance of the shoe: To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, neither nearby a heat source.

		Description	Measure unit	Result	EN345 required
Complete shoe	Protection of toes: steel tip resistant to: » a shock of 200 J » pressure of 1500 kg	Impact resistance (clearance after shock)	mm	15	>14
		Compressive strength (after clearance compression)	mm	17	>14
	Anti-shock system: low-density polyurethane and profile of the heel	Shock absorption in heel	J	>30	>20
Upper	leather, water repellent, grey thickness 1,6mm	Permeability to water vapor	mg/m ² per hour	>2,3	>0,8
		Permeability coefficient	mg/cmq	>25	>20
		Water repellent	minute	20	<60
Front	thickness 1,2mm	Permeability coefficient	mg/cmq	>35	>30
Lining	Cambrella black	Permeability to water vapor	mg/cmq h	>5	>2
Back	thickness 1,0mm	Permeability coefficient	mg/cmq	>45	>30
Insole	Antistatic, absorbent, resistant to abrasion and to exfoliation	Abrasion resistance	cycles	>400	>400
Outsole	Antistatic double density polyurethane, injected directly onto the upper grey, anti-slip, abrasion resistant, mineral oils and weak acids	Abrasion resistance (volume loss)	mm ³	110	<150
		Oil resistance (volume variation AV)	%	1,0+	<12+
		Coefficient of adhesion of the outsole	---	0,18	>0,15



SiTCO
TOTAL PACKAGING SOLUTIONS

شركة الفصول للتجارة والصناعة الدولية

SEASON INTERNATIONAL TRADING & INDUSTRIES CO.

P.O. Box 886, Manama - Kingdom of Bahrain, Tel: +973 17704647, Fax: +973 17704648
E-mail: info@seasoninternational.net, web: www.seasoninternational.net