

The semi-automatic solution with top price/performance ratio



Characteristics

| | | | | | |
|------------------------|------------|-------------|------------------|------------------|------------------|
| Ring diameters: | 50 cm | 90 cm | 125 cm | 160 cm | 200/250 cm |
| Standard film quality: | 23 m μ | 23 m μ | 23 m μ | 23 m μ | 23 m μ |
| Film reel dimensions: | 100 mm | 100, 170 mm | 100, 170, 250 mm | 100, 170, 250 mm | 100, 170, 250 mm |
| Max. ring speed: | 350 rpm | 140 rpm | 70 rpm | 60 rpm | 50 rpm |
| Power supply: | 230 V | 230 V | 230 V | 230 V | 230 V |
| Power consumption: | 0.26 Kw | 0.31 Kw | 0.48 Kw | 0.52 Kw | 0.55 Kw |
| Inverter / PLC: | Omron | Omron | Fuji / Omron | Fuji / Omron | Fuji / Omron |

Advantages

- CE certified
- Proven quality with competitive price
- Easy operation, simple maintenance
- In various inner ring diameters available
- Double film reel dispenser
- Safety foot switch
- Ring protection
- Adjustable stretch film tension
- Adjustable ring speed
- Various optional features, i.e.
 - Automatic film cutter
 - Top press

Chart of types model FV٣٠٠

| Item No. | Model | Inner diameter |
|----------|-----------|----------------|
| 31.3001 | FV50/300 | 50 cm |
| 31.3002 | FV90/300 | 90 cm |
| 31.3003 | FV125/300 | 125 cm |
| 31.3004 | FV160/300 | 160 cm |
| 31.3005 | FV200/300 | 200 cm |
| 31.3006 | FV250/300 | 250 cm |



SiTCO
TOTAL PACKAGING SOLUTIONS

شركة الفصول للتجارة والصناعة الدولية

SEASON INTERNATIONAL TRADING & INDUSTRIES CO.