

## Product sheet **hera** \$\mathbb{B}\$



Product reference	HERA
Euronorm EN345	SB SRC
Sizes	42-36
Weight(s. 41)	340 gr.

**Model Description:** Leather shoe, water repellent, white, Cambrella lining, antistatic, shock proof, anti-slip, steel toe, SB, PU sole.

Application areas: : food, healthcare.

**Precaution and maintenance of the shoe:** To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, neither nearby a heat source.

		Description	Measure unit	Result	EN345 required
Complete shoe	Protection of toes: steel tip resistant to:  » a shock of 200 J	Impact resistance (clearance after shock) Compressive strength (after clearance	mm	15	>14
	» pressure of 1500 kg	compression)	mm	17	>14
	Anti-shock system: low-density polyurethane and profile of the heel	Shock absorption in heel	J	>30	>20
Upper leather, water repellent, white thickness 1,6mm	leather, water repellent, white	Permeability to water vapor	mg/m² per hour		>0,8
	thickness 1,6mm	Permeability coefficient	mg/cmq		>20
		Water repellent	minute		<60
Front	thickness 1,2mm	Permeability coefficient	mg/cmq		>30
Lining	Cambrella grey	Permeability to water vapor	mg/cmq h		>2
Back	thickness 1,0mm	Permeability coefficient	mg/cmq		>30
Insole	Antistatic, absorbent, resistant to abrasion and to exfoliation	Abrasion resistance	cycles	>400	>400
directly white,	Antistatic double density polyurethane, injected directly onto the PU upper	Abrasion resistance (volume loss)	mm3	90	<150
	white, anti-slip, abrasion resistant, mineral oils and weak acids	Oil resistance (volume variation AV)	%	1,0+	<12+
		Coefficient of adhesion of the outsole		0,10	>0,15

