

Pneumatic sealless plastic strapping tool for heavy strapping


Characteristics

Strapping qualities:		Polyester (PET)
Strapping dimensions:	widths	19.0 – 32.0 mm / 3/4 – 1 4/16"
	thicknesses	0.60 – 1.53 mm / .023 – .060"
Weight in cl. bracket:		8.9 kg / 19.6 lbs
Dimension without bracket :		L 372 x W 176 x H 146 mm / 14.7" x 6.9" x 5.7"
Average seal strength:		up to 75 % (dependent on strap quality)
Type of seal:		Friction weld sealing
Strap tension:		2000 – 3500 N / 450 – 785 lbs (adjustable) or
		4000 – 7000 N / 900 – 1570 lbs (adjustable)
Tensioning speed:		120 mm/s / 4.7 inch/s or
		60 mm/s / 2.4 inch/s
Max. air pressure:		6.0 bar / 87 psi
Suspension bracket supplied with the tool		

Advantages

- Unique plastic strapping tool on the market
- The strapping tool can be used in two button (manual) or in one button operation mode (semi-automatic) by turning the adjustment screw for operation mode
- High tension force up to 7000N
- Ideal for heavy duty applications with strapping dimensions of 19 to 32 mm (¾ to 1 ¼") and a thickness up to 1.53 mm (.060")
- Pneumatically powered reliable and service friendly tool
- The strap tension can be adjusted individually using the adjustment system – thus the package is secured with a perfectly tensioned strap
- The sealing time is set individually for a specific strap quality and thickness and a high seal strength is assured

Chart of types model P 359

Item No.	Model	Strap widths		Strap thicknesses		Max. Tension		Tension speed	
		mm	inch	mm	inch	N	lbs	mm/sec.	inch/sec.
49.0503	P 359 /19/0.80-1.53/3.5	19	4/3	0.80-1.53	.031-.060	3500	785	120	4.7
49.0504	P 0.80/19/359 -7.0/1.53	19	4/3	0.80-1.53	.031-.060	7000	1570	60	2.4
49.0511	P 359 /0/25.60-0.79/3.5	25	1	0.60-0.79	.023-.030	3500	785	120	4.7
49.0512	P 359 /0.60/25-0.79/7.0	25	1	0.60-0.79	.023-.030	7000	1570	60	2.4
49.0513	P 359 /0.80/25-1.35/3.5	25	1	0.80-1.35	.031-.053	3500	785	120	4.7
49.0514	P 0.80/25/359 -7.0/1.35	25	1	0.80-1.35	.031-.053	7000	1570	60	2.4
49.0521	P 359 /0.60/32-0.79/3.5	32	1 ¼	0.60-0.79	.023-.030	3500	785	120	4.7
49.0522	P 359 /0/32.60-0.79/7.0	32	1 ¼	0.60-0.79	.023-.030	7000	1570	60	2.4
49.0523	P 359 /0/32.80-1.35/3.5	32	1 ¼	0.80-1.35	.031-.053	3500	785	120	4.7
49.0524	P 0.80/32/359 -7.0/1.35	32	1 ¼	0.80-1.35	.031-.053	7000	1570	60	2.4



SiTCO
TOTAL PACKAGING SOLUTIONS

شركة الفصول للتجارة والصناعة الدولية

SEASON INTERNATIONAL TRADING & INDUSTRIES CO.

P.O. Box 886, Manama - Kingdom of Bahrain, Tel: +973 17704647, Fax: +973 17704648
E-mail: info@seasoninternational.net, web: www.seasoninternational.net